

R134a

ECO COOLER

AIR COOLED CHILLER

STANDARD MODEL

50Hz

150 kW – 2000 kW

2022

ECO COOLER
AIR CONDITIONER

MULTI STAGE EVAPORATIVE COOLING






Special Public places
Commercial, Office, Hospital, Restaurant,
Coffee shop & Etc .

ECO COOLER

AIR CONDITIONER





ECO COOLER

Table of Contents

INTRODUCTION	7
NOMENCLATURE	7
FEATURES AND BENEFITS	8
STANDARD SPECIFICATIONS	9
OPTIONAL FEATURES	15
TECHNICAL DATA	16
PERFORMANCE DATA TABLES	19
UNIT DIMENSIONS	24
Typical electrical wiring diagram	36
TYPICAL WIRING DIAGRAM	37


INTRODUCTION

Eco Cooler connection with customer is permanent and does not lead to sell units. Our motto is making the best environment for people to build a better world to live.

Eco Cooler Air cooled water chillers **EACH** series designed to be suitable for all weather conditions, from cold to moderate to hot climates, the various environment, from residential building to industrial sites with polluted environment. Optimum performance, high efficiency, low power consumption, easy installation and low noise operations are the features of the EACH chillers.

EACH series cooling capacities are available from 45 TR (158 kW) to 430 TR (1512 kW). Models are in two categories of STANDARD (for cold and moderate climates) and HIGH EFFICIENT (for hot and tropical climates) conditions.

NOMENCLATURE



FEATURES AND BENEFITS


- Optimized energy efficiency both at full and part load conditions
- Low operating sound levels are achieved by the latest compressor and fan design
- Stepped and Stepless screw compressor with professional control system to minimize energy consumption and optimize the unit performance.
- Compact design for minimized installation space and small footprint
- One, two, three or four truly independent refrigerant circuits for outstanding reliability
- Using microchannel technology for condenser with higher corrosion resistance and longer life and 30% refrigerant charge compared to traditional solutions.
- Structure and base in hot-dip galvanized steel with electrostatic powder painting.
- Electrical expansion valve: quickly and precisely adapts to the effective load required.
- Connectable to Building Management Systems (BMS) via MODBUS, BACNet and CANBUS protocols.



STANDARD SPECIFICATIONS

SEMI HERMETIC SCREW COMPRESSOR



EACH compressors features mechanical capacity control, which enables very good efficiency and simple system integration. It features mechanical capacity control, which enables very good efficiency and simple system integration. Screw Compressors are equipped to solenoid valve for stepped or stepless capacity control, suction and discharge shut-off valve, oil sight glass, check valve in discharge gas outlet, oil fill/drain service valve, directly flanged on three stage oil separator, robust axial bearings in tandem configuration, internal pressure relief valve as a burst protection and manual lock-out electronic protection system for thermal motor winding temperature, phase reversal, discharge gas temperature protection controls.



STANDARD SPECIFICATIONS

SHELL AND TUBE EVAPORATOR

The evaporator is a high efficiency DX shell & tube heat exchanger design with inner grooved copper tubes roller expanded into the tube sheet. evaporators are tested with a refrigerant side of 30 bars and a water side of 10 bars. Helium leak test is a standard test for evaporators. A guarantee is offered against coolant leak for up to 2 gr/year. Tests are performed at various pressure levels for multi circuit evaporator and prevention of leakage between circuits is guaranteed. Water connections are grooved pipe. Each shell includes a vent, a drain and fittings for temperature control sensors and is insulated with 3/4 inch equal insulation. Evaporator heaters with thermostat are provided to help protect the evaporator from freezing at ambient temperatures down to -29°C.






STANDARD SPECIFICATIONS

CONDENSERS COIL


The condenser coils are built up microchannel technology. Integral NOCOLOK brazing low contact resistance improve the heat transfer performance perfectly. AL-AL structure without electric potential difference makes high corrosion resistance. The advantages of microchannel condensers over finned-tube coil are:

- Smaller diameter, more tube holes and larger internal surface intensify unit capacity as per volume.
- Small cross sectional area makes low air flow resistance, small eddy area and low noise.
- Parallel arrangement of flat tubes enlarge refrigerant circulation area.
- Adjusting the position and quantity of baffles to adapt to refrigerant phase transition and optimize heat transfer and pressure drop.
- The structure effectively breaks air thermal boundary layer, reducing heat exchanging resistance.
- Waving path makes the contacts longer to intensify heat exchanging.



F&T
dust removal difficult - heat transfer loss
high risk of damage during cleaning

MCHE
dust removal easy
immediate performance recovery



STANDARD SPECIFICATIONS

CONDENSER FAN


Direct drive vertical discharge condenser fans are dynamically balanced. Totally enclosed air over motors completely seal the motor windings to prevent exposure to ambient conditions. Three-phase condenser fan motors with permanently lubricated ball bearings and internal thermal overload protection are provided. Improved acoustic performance due to an optimized blade-design external rotor motors comply with protection class IP54. The winding insulation corresponds to insulation class F. Through the use of deep groove ball bearings, closed on both sides, with specially paired grease lubricant, maintenance-free and low-noise operation is guaranteed.



CONTROL PANEL

Chillers are equipped with a latest version of controller designed to ensure energy saving and unit efficiency. Available functions :

- Monitoring operating parameters including water inlet and outlet temperature, suction and discharge temperature, suction and discharge pressure
- Protecting the system from frosting water
- Stepped or stepless Capacity control
- Controlling Fan start/stop with pressure
- Adjusting Fan speed through controlling inverter (as per request)
- Connection to building Management System (BMS) via MODBUS protocol
- keeping all the faults in the alarm history
- Compressors hour equalization



STANDARD SPECIFICATIONS

REFRIGERATION PIPE LINE

- INDEPENDENT REFRIGERATION CIRCUIT PER COMPRESSOR
- ELECTRONIC EXPANSION VALVE: Used to regulate the refrigerant flow to the evaporator and maintain a constant superheat and provide capacity required.
- LIQUID LINE REPLACEABLE CORE TYPE FILTER DRIER: Refrigerant circuits are kept free of harmful moisture, sludge, acids and oil contaminating particles by the filter drier.



- LIQUID LINE MOISTURE INDICATOR SIGHT GLASS: Installed in the liquid line. An easy-to-read color indicator shows moisture contents and provides a mean for checking the system refrigerant charge.
- LIQUID, DISCHARGE AND SUCTION LINES SHUT OFF VALVE
- DISCHARGE, SUCTION AND LIQUID LINE PIPES: All pipelines are sized to minimize pressure drop and keep proper velocity ensuring oil return.
- LIQUID INJECTION KIT: For cooling the compressor in high compressor discharge temperature.

STANDARD SPECIFICATIONS

ELECTRICAL PANEL

- COMPRESSOR PART WINDING START
- COMPRESSOR IN-BUILT PROTECTION DEVICE
- STARTER: The starter is operated by the control circuit and provides power to the compressor motors. These devices are rated to handle safely both RLA and LRA of motors.
- CRANKCASE HEATERS: Each compressor has immersion type crankcase heater. The compressor crankcase heater is always on when the compressors are de-energized. This protects the system against refrigerant Migration, oil dilution and potential compressor failure.
- HIGH PRESSURE SWITCH: This switch provides an additional safety protection in case of excessive discharge pressure.
- LOW PRESSURE SWITCH: This switch provides an additional safety protection in case of very low suction pressure to avoid water freezing.
- UNIT ON-OFF SWITCH: On Off Switch is provided for manually switching the unit control circuit.
- INDICATOR LIGHTS: LED lights indicates power ON to the units, MENU adjustment and FAULT indications due to trip on safety devices.
- UNDER VOLTAGE AND PHASE PROTECTION: This feature protects the chiller against low incoming voltage as well as single phasing , phase reversal and phase imbalance by de-energizing the control circuit.
- FAN MOTOR CIRCUIT BREAKER: For each pair of condenser fan motor.
- COMPRESSOR CIRCUIT BREAKERS: Protects compressor against overload and short circuit. When tripped, the breaker opens the power supply to the compressor and control circuit through auxiliary contacts. These circuit breakers are provided with thermal adjustable switch for precise overload setting.
- EXTERNAL OVERLOAD RELAY FOR EACH COMPRESSOR
- CONTROL FUSED FOR SHORT CIRCUIT PROTECTION

OPTIONAL FEATURES



- **WATER FLOW SWITCH:** Paddle type field adjustable flow switch for water cooler circuits, Interlock into safety circuits so that the unit will remain off unit water flow is determine.
- **UNIT MOUNTING SPRING ISOLATORS:** This housed spring assemblies have a neoprene friction pad on the bottom to prevent vibration transmission.
- **COMPRESSOR SILENCER BOX:** reduces the compressor operating noise and keeps the compressor clean.
- **COPPER FINS/TUBES CONDENSER COILS:** For seashore salty corrosive environments.
- **PRE-COATED ALUMINUM FINS CONDENSER COILS (MHG):** For seashore or acid corrosive environments.
- **BUILDING MANAGEMENT SYSTEM (BMS):** MODBUS, BACNET, and CANBUS protocol
- **NON-FUSED MAIN DISCONNECT SWITCHES:** De-energize power supply during servicing/repair works as well as with door interlock.
- **EVAORATOR HEATER TAPE:** Prevent freezing up of water on low ambient.
- **GROUND CURRENT PROTECTION:** Additional protection for compressor in the case of abnormal current leakage.

TECHNICAL DATA

UNIT MODEL (EACH)		45	50	55	60	70	80	90	100	115	130	140	150
COOLING CAPACITY*	RT	48.9	50.9	53.9	58.9	75.1	86.9	96.6	105.9	116.1	137.4	149.0	149.0
	kW	171.0	178.3	188.5	206.2	262.8	304.2	338.2	370.7	406.5	481.1	521.4	521.4
POWER INPUT (kW)		48.5	52.8	56.9	57.8	79.5	83.0	96.8	114.6	115.4	137.0	158.5	158.5
TOTAL EER (W/W)		3.2	3.0	3.0	3.2	3.0	3.2	3.1	2.9	3.1	3.2	3.0	3.0
COMPRESSOR		Semi Hermetic Compact Screw											
QUANTITY (No.)		1						2					
OIL GRADE		BSE170 Or Equivalent											
OIL CHARGE PER COMPRESSOR (Liter)		15	22	15	22	19	15	15	15	22	22	19	19
CAPACITY CONTROL (%) (STEPPED)		100-25											
CONDENSER TYPE		MICRO CHANNEL											
CONDENSER QTY (No.)		6	6	6	8	8	12	12	12	8	8	8	8
TOTAL FACE AREA (m ²)		6.0	6.0	6.0	8.0	8.0	12.0	12.0	12.0	16.0	16.0	16.0	16.0
CONDENSER FAN		Propeller Direct Driven , 800mm dia , 920 rpm											
FAN QTY (No.)		3	3	3	4	4	6	6	6	8	8	8	8
AIR FLOW RATE (m ³ /h)		67500	67500	67500	90000	90000	135000	135000	135000	180000	180000	180000	180000
MOTOR POWER FAN (kW)		5.7	5.7	5.7	7.6	7.6	11.4	11.4	11.4	15.2	15.2	15.2	15.2
EVAPORATOR		Direct Expansion Shell & Tube											
EVAPORATOR QTY (No.)		1											
WATER FLOW RATE (m ³ /h)		26.6	27.7	29.3	32.1	40.9	47.4	52.6	57.7	63.3	74.9	81.2	81.2
WATER VOLUME PER COOLER (Liter)		128	128	128	128	172	167	167	167	166	277	277	277
WATER CONNECTION SIZE (IN/OUT) DIAMETER (mm)		125	125	125	125	150	150	150	150	150	150	150	150
EXPANSION VALVE		Electronic											
POWER REQUIREMENT		400V/3PH/50Hz											
REFRIGERATION CIRCUITS (No.)		1						2					
APPROXIMATE WEIGHT (kg)		1232	1542	1237	1651	1791	2241	2286	2336	3170	3350	3390	3390
DIMENSION	HEIGHT (m)	2.59	2.59	2.59	2.59	2.59	2.59	2.59	2.59	2.59	2.59	2.59	2.59
	WIDTH (m)	1.27	1.27	1.27	1.27	1.27	1.27	1.27	1.27	2.27	2.27	2.27	2.27
	LENGTH (m)	2.91	2.91	2.91	3.88	3.88	5.82	5.82	5.82	3.88	3.88	3.88	3.88

*Capacity rating are based on Standard ARI-550/590 conditions of: 35 °C (95 °F) ambient/ 7 °C (44.6 °F) Leaving Chilled Water Temperature / 5 °C (9 °F) Inlet-Outlet Water Temperature Difference/ 0.018 m².°C/kW (0.0001 ft². h.°F /Btu) Fouling Factor

TECHNICAL DATA

UNIT MODEL (EACH)		160	170	180	190	200	220	230	240	250	260	270	280
COOLING CAPACITY*	RT	171.0	171.0	200.3	200.3	200.3	236.0	236.0	236.0	269.7	269.7	269.7	269.7
	kW	598.5	598.5	701.0	701.0	701.0	825.9	825.9	825.9	944.0	944.0	944.0	944.0
POWER INPUT (kW)		175.3	175.3	204.0	204.0	204.0	228.0	228.0	228.0	265.2	265.2	265.2	265.2
TOTAL EER (W/W)		3.1	3.1	3.1	3.1	3.1	3.2	3.2	3.2	3.2	3.2	3.2	3.2
COMPRESSOR		Semi Hermetic Compact Screw											
QUANTITY (No.)		2											
OIL GRADE		BSE170 Or Equivalent											
OIL CHARGE PER COMPRESSOR (Liter)		19	19	30	30	30	30	30	30	30	30	30	30
CAPACITY CONTROL (%) (STEPPED)		100-25											
CONDENSER TYPE		MICRO CHANNEL											
CONDENSER QTY (No.)		10	10	12	12	12	14	14	14	16	16	16	16
TOTAL FACE AREA (m ²)		20.0	20.0	24.0	24.0	24.0	28.0	28.0	28.0	32.0	32.0	32.0	32.0
CONDENSER FAN		Propeller Direct Driven , 800mm dia , 920 rpm											
FAN QTY (No.)		10	10	12	12	12	14	14	14	16	16	16	16
AIR FLOW RATE (m ³ /h)		225000	225000	270000	270000	270000	315000	315000	315000	360000	360000	360000	360000
MOTOR POWER FAN (kW)		19	19	22.8	22.8	22.8	26.6	26.6	26.6	30.4	30.4	30.4	30.4
EVAPORATOR		Direct Expansion Shell & Tube											
EVAPORATOR QTY (No.)		1											
WATER FLOW RATE (m ³ /h)		93.2	93.2	109.1	109.1	109.1	128.6	128.6	128.6	146.9	146.9	146.9	146.9
WATER VOLUME PER COOLER (Liter)		260	260	240	240	240	470	470	470	440	440	440	440
WATER CONNECTION SIZE (IN /OUT) DIAMETER (mm)		150	150	150	150	150	200	200	200	200	200	200	200
EXPANSION VALVE		Electronic											
POWER REQUIREMENT		400V/3PH/50Hz											
REFRIGERATION CIRCUITS (No.)		2											
APPROXIMATE WEIGHT (kg)		3675	3675	4779	4779	4779	5283	5283	5283	5698	5698	5698	5698
DIMENSION	HEIGHT (m)	2.59	2.59	2.59	2.59	2.59	2.59	2.59	2.59	2.59	2.59	2.59	2.59
	WIDTH (m)	2.27	2.27	2.27	2.27	2.27	2.27	2.27	2.27	2.27	2.27	2.27	2.27
	LENGTH (m)	4.85	4.85	5.82	5.82	5.82	6.79	6.79	6.79	7.76	7.76	7.76	7.76

*Capacity rating are based on Standard ARI-550/590 conditions of: 35 °C (95 °F) ambient/ 7 °C (44.6 °F) Leaving Chilled Water Temperature / 5 °C (9 °F) Inlet-Outlet Water Temperature Difference/ 0.018 m².°C/kW (0.0001 ft². h.°F/Btu) Fouling Factor

TECHNICAL DATA

UNIT MODEL (EACH)		300	320	330	340	350	360	380	400	420	430	440	450
COOLING CAPACITY*	RT	312.2	327.2	327.2	358.5	358.5	358.5	409.4	409.4	454.0	454.0	454.0	454.0
	kW	1092.5	1145.3	1145.3	1254.7	1254.7	1254.7	1432.9	1432.9	1589.1	1589.1	1589.1	1589.1
POWER INPUT (kW)		301.8	349.7	349.7	374.0	374.0	374.0	398.8	398.8	449.7	449.7	449.7	449.7
TOTAL EER (W/W)		3.3	3.0	3.0	3.0	3.0	3.0	3.2	3.2	3.2	3.2	3.2	3.2
COMPRESSOR		Semi Hermetic Compact Screw											
QUANTITY (No.)		2						3					
OIL GRADE		BSE170 Or Equivalent											
OIL CHARGE PER COMPRESSOR (Liter)		30	32	32	32	32	32	30	30	30	30	30	30
CAPACITY CONTROL (%) (STEPPED)		100-25											
CONDENSER TYPE		MICRO CHANNEL											
CONDENSER QTY (No.)		18	18	18	20	20	20	24	24	27	27	27	27
TOTAL FACE AREA (m ²)		36.0	36.0	36.0	40.0	40.0	40.0	48.0	48.0	54.0	54.0	54.0	54.0
CONDENSER FAN		Propeller Direct Driven , 800mm dia , 920 rpm											
FAN QTY (No.)		18	18	18	20	20	20	24	24	27	27	27	27
AIR FLOW RATE (m ³ /h)		405000	405000	405000	450000	450000	450000	540000	540000	607500	607500	607500	607500
MOTOR POWER FAN (kW)		34.2	34.2	34.2	38	38	38	45.6	45.6	51.3	51.3	51.3	51.3
EVAPORATOR		Direct Expansion Shell & Tube											
EVAPORATOR QTY (No.)		1											
WATER FLOW RATE (m ³ /h)		170.1	178.3	178.3	195.3	195.3	195.3	223.0	223.0	247.4	247.4	247.4	247.4
WATER VOLUME PER COOLER (Liter)		590	590	590	550	550	550	660	660	660	660	660	660
WATER CONNECTION SIZE (IN /OUT) DIAMETER (mm)		250	250	250	250	250	250	250	250	250	250	250	250
EXPANSION VALVE		Electronic											
POWER REQUIREMENT		400V/3PH/50Hz											
REFRIGERATION CIRCUITS (No.)		2						3					
APPROXIMATE WEIGHT (kg)		6242	6422	6422	6826	6826	6826	8685	8685	9145	9145	9145	9145
DIMENSION	HEIGHT (m)	2.59	2.59	2.59	2.59	2.59	2.59	2.59	2.59	2.59	2.59	2.59	2.59
	WIDTH (m)	2.27	2.27	2.27	2.27	2.27	2.27	2.27	2.27	2.27	2.27	2.27	2.27
	LENGTH (m)	8.73	8.73	8.73	9.7	9.7	9.7	11.64	11.64	13.58	13.58	13.58	13.58

*Capacity rating are based on Standard ARI-550/590 conditions of: 35 °C (95 °F) ambient / 7 °C (44.6 °F) Leaving Chilled Water Temperature / 5 °C (9 °F) Inlet-Outlet Water Temperature Difference/ 0.018 m².°C/kW (0.0001 ft². h.°F /Btu) Fouling Factor

PERFORMANCE DATA TABLES

LEAVING CHILLED WATER TEMP. (LCWT)	UNIT SIZE	30°C (86°F) AMBIENT TEMPERATURE				
		COOLING CAPACITY		COMP. POWER (kW)	Total EER (W/W)	WATER FLOW (m³/h)
		RT	kW			
7°C	EACH-45	51.5	180.1	45.1	3.5	28
	EACH-50	53.5	187.2	48.4	3.5	29.1
	EACH-55	59.5	208.2	43.2	4.3	32.4
	EACH-60	61.4	214.9	55.1	3.4	33.4
	EACH-70	79.5	278.2	72.4	3.5	43.3
	EACH-80	91.2	319.1	79.6	3.5	49.7
	EACH-90	101.6	355.8	90.4	3.5	55.4
	EACH-100	111.9	391.7	105.1	3.4	61
	EACH-115	121	423.5	110.3	3.4	65.9
	EACH-130	145.6	509.6	125.3	3.6	79.3
	EACH-140	157.7	552	144.5	3.5	85.9
	EACH-150	157.7	552	144.5	3.5	85.9
	EACH-160	180.8	632.8	160.4	3.5	98.5
	EACH-170	180.8	632.8	160.4	3.5	98.5
	EACH-180	211.8	741.3	187.9	3.5	115.4
	EACH-190	211.8	741.3	187.9	3.5	115.4
	EACH-200	211.8	741.3	187.9	3.5	115.4
	EACH-220	249	871.5	212	3.7	135.7
	EACH-230	249	871.5	212	3.7	135.7
	EACH-240	249	871.5	212	3.7	135.7
	EACH-250	283.7	992.8	244.8	3.6	154.5
	EACH-260	283.7	992.8	244.8	3.6	154.5
	EACH-270	283.7	992.8	244.8	3.6	154.5
	EACH-280	283.7	992.8	244.8	3.6	154.5
	EACH-300	328.6	1150.1	276.5	3.7	179
	EACH-320	345.7	1210.1	322	3.4	188.4
	EACH-330	345.7	1210.1	322	3.4	188.4
	EACH-340	378.2	1323.6	343.3	3.5	206
	EACH-350	378.2	1323.6	343.3	3.5	206
	EACH-360	378.2	1323.6	343.3	3.5	206
EACH-380	430.7	1507.4	366.8	3.7	234.6	
EACH-400	430.7	1507.4	366.8	3.7	234.6	
EACH-420	477.1	1669.7	414.8	3.6	259.9	
EACH-430	477.1	1669.7	414.8	3.6	259.9	
EACH-440	477.1	1669.7	414.8	3.6	259.9	
EACH-450	477.1	1669.7	414.8	3.6	259.9	

1- ECHA Chillers are rated based on Standard ARI-550/590-98 conditions of: 5 °C (9 °F) Inlet/Outlet Water Temperature Difference and 0.018 m². °C/kW (0.0001 ft². h. °F /Btu) Fouling Factor

2- Direct interpolation is permissible. Do not extrapolate.

3- Energy Efficiency Ratio (EER) is for the overall unit, refer to electrical data for fan power input.

PERFORMANCE DATA TABLES

LEAVING CHILLED WATER TEMP. (LCWT)	UNIT SIZE	35°C (95°F) AMBIENT TEMPERATURE				
		COOLING CAPACITY		COMP. POWER (kW)	Total EER (W/W)	WATER FLOW (m³/h)
		RT	kW			
7°C	EACH-45	48.9	171	48.5	3.2	26.6
	EACH-50	50.9	178.3	52.8	3	27.7
	EACH-55	53.9	188.5	56.9	3	29.3
	EACH-60	58.9	206.2	57.8	3.2	32.1
	EACH-70	75.1	262.8	79.5	3	40.9
	EACH-80	86.9	304.2	83	3.2	47.4
	EACH-90	96.6	338.2	96.8	3.1	52.6
	EACH-100	105.9	370.7	114.6	2.9	57.7
	EACH-115	116.1	406.5	115.4	3.1	63.3
	EACH-130	137.4	481.1	137	3.2	74.9
	EACH-140	149	521.4	158.5	3	81.2
	EACH-150	149	521.4	158.5	3	81.2
	EACH-160	171	598.5	175.3	3.1	93.2
	EACH-170	171	598.5	175.3	3.1	93.2
	EACH-180	200.3	701	204	3.1	109.1
	EACH-190	200.3	701	204	3.1	109.1
	EACH-200	200.3	701	204	3.1	109.1
	EACH-220	236	825.9	228	3.2	128.6
	EACH-230	236	825.9	228	3.2	128.6
	EACH-240	236	825.9	228	3.2	128.6
	EACH-250	269.7	944	265.2	3.2	146.9
	EACH-260	269.7	944	265.2	3.2	146.9
	EACH-270	269.7	944	265.2	3.2	146.9
	EACH-280	269.7	944	265.2	3.2	146.9
	EACH-300	312.2	1092.5	301.8	3.3	170.1
	EACH-320	327.2	1145.3	349.7	3	178.3
	EACH-330	327.2	1145.3	349.7	3	178.3
	EACH-340	358.5	1254.7	374	3	195.3
	EACH-350	358.5	1254.7	374	3	195.3
	EACH-360	358.5	1254.7	374	3	195.3
EACH-380	409.4	1432.9	398.8	3.2	223	
EACH-400	409.4	1432.9	398.8	3.2	223	
EACH-420	454	1589.1	449.7	3.2	247.4	
EACH-430	454	1589.1	449.7	3.2	247.4	
EACH-440	454	1589.1	449.7	3.2	247.4	
EACH-450	454	1589.1	449.7	3.2	247.4	

1- ECHA Chillers are rated based on Standard ARI-550/590-98 conditions of: 5 °C (9 °F) Inlet/Outlet Water Temperature Difference and 0.018 m².°C/kW (0.0001 ft². h.°F /Btu) Fouling Factor

2- Direct interpolation is permissible. Do not extrapolate.

3- Energy Efficiency Ratio (EER) is for the overall unit, refer to electrical data for fan power input.

PERFORMANCE DATA TABLES

LEAVING CHILLED WATER TEMP. (LCWT)	UNIT SIZE	40°C (104°F) AMBIENT TEMPERATURE				
		COOLING CAPACITY		COMP. POWER (kW)	Total EER (W/W)	WATER FLOW (m ³ /h)
		RT	kW			
7°C	EACH-45	45.9	160.6	53.4	2.7	25
	EACH-50	47.8	167.5	58.2	2.6	26.1
	EACH-55	50.4	176.6	62.5	2.6	27.5
	EACH-60	55.6	194.7	63.8	2.7	30.3
	EACH-70	70.5	246.7	87.6	2.6	38.4
	EACH-80	81.4	284.8	91.1	2.8	44.3
	EACH-90	91.1	318.7	106.3	2.7	49.6
	EACH-100	99.6	348.6	125.6	2.5	54.3
	EACH-115	109.6	383.7	127.2	2.7	59.7
	EACH-130	128.8	450.9	150.9	2.7	70.2
	EACH-140	139.8	489.4	174.8	2.6	76.2
	EACH-150	139.8	489.4	174.8	2.6	76.2
	EACH-160	160.7	562.5	193.3	2.6	87.6
	EACH-170	160.7	562.5	193.3	2.6	87.6
	EACH-180	187.8	657.5	224	2.7	102.3
	EACH-190	187.8	657.5	224	2.7	102.3
	EACH-200	187.8	657.5	224	2.7	102.3
	EACH-220	221.7	775.8	248.2	2.8	120.8
	EACH-230	221.7	775.8	248.2	2.8	120.8
	EACH-240	221.7	775.8	248.2	2.8	120.8
	EACH-250	254.6	891.1	290.9	2.8	138.7
	EACH-260	254.6	891.1	290.9	2.8	138.7
	EACH-270	254.6	891.1	290.9	2.8	138.7
	EACH-280	254.6	891.1	290.9	2.8	138.7
	EACH-300	294.6	1031	330.8	2.8	160.5
	EACH-320	308.1	1078.2	380.3	2.6	167.8
	EACH-330	308.1	1078.2	380.3	2.6	167.8
	EACH-340	338.3	1184.1	407.4	2.7	184.3
	EACH-350	338.3	1184.1	407.4	2.7	184.3
	EACH-360	338.3	1184.1	407.4	2.7	184.3
EACH-380	386.4	1352.4	437.2	2.8	210.5	
EACH-400	386.4	1352.4	437.2	2.8	210.5	
EACH-420	428.5	1499.6	492.9	2.8	233.4	
EACH-430	428.5	1499.6	492.9	2.8	233.4	
EACH-440	428.5	1499.6	492.9	2.8	233.4	
EACH-450	428.5	1499.6	492.9	2.8	233.4	

1- ECHA Chillers are rated based on Standard ARI-550/590-98 conditions of: 5 °C (9 °F) Inlet/Outlet Water Temperature Difference and 0.018 m².°C/kW (0.0001 ft². h.°F /Btu) Fouling Factor

2- Direct interpolation is permissible. Do not extrapolate.

3- Energy Efficiency Ratio (EER) is for the overall unit, refer to electrical data for fan power input.

PERFORMANCE DATA TABLES

LEAVING CHILLED WATER TEMP. (LCWT)	UNIT SIZE	45°C (113°F) AMBIENT TEMPERATURE				
		COOLING CAPACITY		COMP. POWER (kW)	Total EER (W/W)	WATER FLOW (m ³ /h)
		RT	kW			
7°C	EACH-45	42.8	149.8	58.8	2.3	23.3
	EACH-50	44.8	156.7	64.5	2.2	24.4
	EACH-55	46.9	164.2	69.1	2.2	25.6
	EACH-60	52.2	182.7	70.5	2.3	28.4
	EACH-70	65.8	230.3	97	2.2	35.8
	EACH-80	75.5	264.4	100.1	2.4	41.2
	EACH-90	84.8	296.7	117.4	2.3	46.2
	EACH-100	92.9	325.3	138.2	2.2	50.6
	EACH-115	102.9	360	140.8	2.3	56
	EACH-130	120.2	420.5	167	2.3	65.5
	EACH-140	130.6	457	193.6	2.2	71.1
	EACH-150	130.6	457	193.6	2.2	71.1
	EACH-160	150.2	525.8	214.2	2.3	81.9
	EACH-170	150.2	525.8	214.2	2.3	81.9
	EACH-180	175.1	612.8	245.8	2.3	95.4
	EACH-190	175.1	612.8	245.8	2.3	95.4
	EACH-200	175.1	612.8	245.8	2.3	95.4
	EACH-220	207.1	724.9	271.2	2.4	112.8
	EACH-230	207.1	724.9	271.2	2.4	112.8
	EACH-240	207.1	724.9	271.2	2.4	112.8
	EACH-250	239	836.4	318.6	2.4	130.2
	EACH-260	239	836.4	318.6	2.4	130.2
	EACH-270	239	836.4	318.6	2.4	130.2
	EACH-280	239	836.4	318.6	2.4	130.2
	EACH-300	276.2	966.7	361.9	2.4	150.5
	EACH-320	288.7	1010.4	414.8	2.3	157.3
	EACH-330	288.7	1010.4	414.8	2.3	157.3
	EACH-340	317.5	1111.1	444.5	2.3	173
	EACH-350	317.5	1111.1	444.5	2.3	173
	EACH-360	317.5	1111.1	444.5	2.3	173
EACH-380	362.8	1269.7	478.9	2.4	197.6	
EACH-400	362.8	1269.7	478.9	2.4	197.6	
EACH-420	401.9	1406.5	539.8	2.4	218.9	
EACH-430	401.9	1406.5	539.8	2.4	218.9	
EACH-440	401.9	1406.5	539.8	2.4	218.9	
EACH-450	401.9	1406.5	539.8	2.4	218.9	

1- ECHA Chillers are rated based on Standard ARI-550/590-98 conditions of: 5 °C (9 °F) Inlet/Outlet Water Temperature Difference and 0.018 m².°C/kW (0.0001 ft². h.°F /Btu) Fouling Factor

2- Direct interpolation is permissible. Do not extrapolate.

3- Energy Efficiency Ratio (EER) is for the overall unit, refer to electrical data for fan power input.

PERFORMANCE DATA TABLES

LEAVING CHILLED WATER TEMP. (LCWT)	UNIT SIZE	50°C (122°F) AMBIENT TEMPERATURE				
		COOLING CAPACITY		COMP. POWER (kW)	Total EER (W/W)	WATER FLOW (m³/h)
		RT	kW			
7°C	EACH-45	39.6	138.6	65.5	2.1	21.6
	EACH-50	41.7	145.8	71.7	2	22.7
	EACH-55	43.2	151.2	77	2	23.5
	EACH-60	48.6	170.1	78.3	2.2	26.5
	EACH-70	61	213.6	107.7	2	33.3
	EACH-80	69.4	243	110.1	2.2	37.8
	EACH-90	78.2	273.5	130.5	2.1	42.6
	EACH-100	86.1	301.4	152.3	2	46.9
	EACH-115	95.8	335.3	156.4	2.1	52.2
	EACH-130	111.7	391	185.5	2.1	60.9
	EACH-140	120.9	423.2	214.9	2	65.9
	EACH-150	120.9	423.2	214.9	2	65.9
	EACH-160	139.4	487.7	238	2	75.9
	EACH-170	139.4	487.7	238	2	75.9
	EACH-180	161.8	566.3	269.3	2.1	88.1
	EACH-190	161.8	566.3	269.3	2.1	88.1
	EACH-200	161.8	566.3	269.3	2.1	88.1
	EACH-220	192.9	675	297.3	2.3	105.1
	EACH-230	192.9	675	297.3	2.3	105.1
	EACH-240	192.9	675	297.3	2.3	105.1
	EACH-250	222.8	779.9	348.4	2.2	121.4
	EACH-260	222.8	779.9	348.4	2.2	121.4
	EACH-270	222.8	779.9	348.4	2.2	121.4
	EACH-280	222.8	779.9	348.4	2.2	121.4
	EACH-300	258.5	904.7	395.9	2.3	140.8
	EACH-320	262.6	919.1	468.2	2	143.1
	EACH-330	262.6	919.1	468.2	2	143.1
	EACH-340	295.9	1035.8	485.8	2.1	161.2
	EACH-350	295.9	1035.8	485.8	2.1	161.2
	EACH-360	295.9	1035.8	485.8	2.1	161.2
EACH-380	338.3	1184.1	523.8	2.3	184.3	
EACH-400	338.3	1184.1	523.8	2.3	184.3	
EACH-420	374.8	1312	590.4	2.2	204.2	
EACH-430	374.8	1312	590.4	2.2	204.2	
EACH-440	374.8	1312	590.4	2.2	204.2	
EACH-450	374.8	1312	590.4	2.2	204.2	






1- ECHA Chillers are rated based on Standard ARI-550/590-98 conditions of: 5 °C (9 °F) Inlet/Outlet Water Temperature Difference and 0.018 m². °C/kW (0.0001 ft². h. °F /Btu) Fouling Factor

2- Direct interpolation is permissible. Do not extrapolate.

3- Energy Efficiency Ratio (EER) is for the overall unit, refer to electrical data for fan power input.




UNIT DIMENSIONS

EACH 45-50-55-60






UNIT DIMENSIONS

EACH 70








UNIT DIMENSIONS

EACH 80








UNIT DIMENSIONS

EACH 90-100-115








UNIT DIMENSIONS

EACH 130-140-150








UNIT DIMENSIONS

EACH 160-170








UNIT DIMENSIONS

EACH 180-190-200







UNIT DIMENSIONS

EACH 220-230-240








UNIT DIMENSIONS

EACH 250-260-270-280






UNIT DIMENSIONS






UNIT DIMENSIONS

EACH 300-320




UNIT DIMENSIONS


EACH 330-340-350




Typical electrical wiring diagram



TYPICAL WIRING DIAGRAM



Power Circuit





. NOTE .

A large rectangular area with rounded corners, outlined in light blue, containing numerous horizontal light blue lines for writing. The lines are evenly spaced and extend across the width of the page, providing a template for taking notes.

ECO COOLER
AIR CONDITIONER